



(19)

---

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 808 151 B1

(12)

# EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:

22.08.2001 Bulletin 2001/34

(21) Application number: 96903663.1

(22) Date of filing: 24.01.1996

(51) Int Cl.7: A61K 7/50

(86) International application number:  
PCT/US96/00989

(87) International publication number:  
WO 96/24329 (15.08.1996 Gazette 1996/37)

**(54) PERSONAL CARE COMPOSITIONS AND WIPE PRODUCTS CONTAINING THE COMPOSITIONS**

KÖRPERPFLEGEMITTEL UND DIESE MITTEL ENTHALTENDE WISCHTÜCHER

#### **COMPOSITIONS DE SOINS CORPORELS ET SERVIETTES LES CONTENANT**

**(84) Designated Contracting States:**

Designated Contracting States:  
**AT BE CH DE DK ES FR GB GR IE IT LI LU NL PT  
SE**

(30) Priority: 10.02.1995 US 386973

(43) Date of publication of application:  
**26.11.1997 Bulletin 1997/48**

(73) Proprietor: THE PROCTER & GAMBLE COMPANY  
Cincinnati, Ohio 45202 (US)

(72) Inventors:

- **BLIESZNER, Kathleen, Clare**  
**Cincinnati, OH 45224 (US)**
  - **DECKNER, George, Endell**  
**Cincinnati, OH 45249 (US)**

(74) Representative: Kohl, Sonia et al  
Procter & Gamble  
European Service GmbH  
Sulzbacher Strasse 40-50  
65824 Schwalbach am Taunus (D)

- DATABASE WPI Section Ch, Week 9210 Derwent Publications Ltd., London, GB; Class A96, AN 92-076737 XP002004684 & JP,A,04 021 625 (KAO CORP), 24 January 1992

**Description****Field of the Invention**

[0001] The present invention relates to personal care compositions, more particularly personal cleansing and/or skin treating compositions. The compositions are useful, for example, for perineal cleansing and protection against perineal dermatitis.

**Background of the Invention**

[0002] Perineal dermatitis (including diaper dermatitis) has been defined as contact dermatitis in the perineal area, including the perineum, buttocks, and the perianal, coccyx and upper/inner thigh regions (Brown DS, Sears M., Perineal Dermatitis: A Conceptual Framework, Ostomy/Wound Management 1993, 39 (7), 20-25). The physical signs of perineal dermatitis may include one or a combination of erythema, swelling, oozing, vesiculation, crusting and scaling, with the possibility of excoriation, thickening and hyper-pigmentation over time (Brown).

[0003] Perineal dermatitis is believed to be caused by the prolonged contact of the skin with body waste such as urine and feces. Although the exact component(s) of body waste responsible for perineal dermatitis has not been identified, factors that are suspected of causing perineal dermatitis include ammonia, moisture, bacteria, urine pH, and Candida albicans. Because these various suspected factors have different properties and require different therapies, one of the most effective methods of treating perineal dermatitis has been the application of a topical protective barrier agent between the skin and the body waste.

[0004] Several topically applied barrier agents are or have been commercially available. Exemplary agents are listed, for example, in U.S. Patent 5,043,155 issued to Puchalski et al. on August 27, 1991. Such agents are typically in the form of powders, lotions, creams and ointments and may contain a variety of ingredients. For example, the agents listed in the U.S. Patent 5,043,155 may contain calcium undecylenate, talc, starch, calcium carbonate, petrolatum, cod liver oil, vitamins A and D, lanolin, balsam, silicone, including dimethicone, zinc oxide, bismuth subnitrate, benzalkonium chloride, methylbenzethonium chloride, and protein hydrolysate containing amino acids.

[0005] Skin protectant agents, for example, dimethicone, are also disclosed in the Federal Register, Vol. 48, No. 32, February 15, 1983, pages 6820-6833 (proposed rule of the U.S. Dept. of Health and Human Services, Federal Food and Drug Administration). Skin protectant drug products for over-the-counter human use, such as diaper rash products, which may include, for example, dimethicone, are discussed in the Federal Register, Vol. 55, No. 119, June 20, 1990, pages 25204-25232 (proposed rule of the U.S. Dept. of Health

& Human Services, Federal Food and Drug Administration).

[0006] Known personal cleansing compositions may contain very small amounts of anti-foaming agents, e.g., silicone oils. Such anti-foaming agents are typically employed in amounts of less than about 0.01 weight % of the composition. Such minute amounts do not provide any significant benefits to the skin.

[0007] Barrier agents for protection against perineal dermatitis may be applied by sprinkling the agent onto the skin, by massaging the material into the skin with the hands, or via a wiping material. Wiping materials are typically used for cleansing while changing an infant diaper or adult incontinence article. Disposable wipes are pre-moistened, disposable towelettes. The towelette is typically a nonwoven formed of various combinations of cellulosic fibers, synthetic polymeric fibers such as polyester, polypropylene and the like, and binders. The nonwoven is generally moistened with a composition containing water (94% or more) and various combinations of other ingredients including moistening agents or humectants, emollients, surfactants, emulsifiers, antimicrobial agents, skin protectants, pH-adjusting agents, fragrances, powders and the like. Several exemplary ingredients that may be used in disposable baby wipes are disclosed in the above referenced U.S. Patent 5,043,155.

[0008] As recognized in U. S. Patent No. 5,043,155, many wipes have historically required the separate application of a barrier agent. More recently, wipes that are said to cleanse and carry a skin protectant onto the skin have become commercially available. An example of such wipes are Baby Fresh With Ultra Guard® baby wipes. The Baby Fresh® baby wipes are marketed with a patent marking of U.S. Patent No. 4,904,524 (issued to Yoh on February 27, 1990).

[0009] It is desirable that, in addition to providing effective cleansing, the wipe itself leave a substantive, highly protective residue on the skin. In order to provide maximum protection against perineal dermatitis, it is desirable that compositions used in wipe products be highly homogeneous. Thus, the components should be homogeneously distributed in the composition so as to provide consistent application of the composition to, or distribution of the composition in, wipe substrates, the skin, or other surfaces. It is also desirable for the composition to rapidly de-emulsify upon application to the skin, and to resist re-emulsification after such application.

[0010] The residue left by a wipe should also have several properties. The residue should protect the skin against irritants accompanying body waste, yet should not significantly reduce transepidermal moisture loss, i.e., the skin should be allowed to breathe even in the presence of the residue (thus, the residue is non-occlusive). Occlusive barrier agents tend to cause excess hydration of the skin, which renders the skin more susceptible to irritation or infection. Moreover, it is desirable for the residue to provide easier cleansing of the perineal

region.

[0011] In addition, it is often desirable that the residue and the wipe provide a favorable esthetic, particularly tactile, perception to the user of the wipe (the user of the wipe may be a wearer of an incontinence article or a care-giver to such wearer). For example, the residue and the wipe should not be excessively greasy, oily, or tacky and should provide an impression of softness or silkiness. The residue should have a sufficiently low coefficient of friction to minimize the risk of skin abrasion or red-marking, and to improve the spreadability of other protective barrier agents that may be applied. The wipe should provide an impression of sufficient wetness and should feel soft and non-irritating to the user.

[0012] Finally, the composition used in the disposable wipe should not negatively impact the physical properties of the nonwoven substrate so as to excessively reduce its utility for the intended application. In addition, the composition should inhibit the growth of a broad range of bacteria, fungi and other microorganisms.

[0013] While the art has provided several compositions having various levels of utility in personal cleansing or treatment for the prevention of perineal dermatitis, the art has not provided the desirable characteristics of such compositions in the manner or to the extent of the present invention.

[0014] It is therefore an object of the present invention to provide a composition that is useful for personal cleansing and for reducing the risk of perineal dermatitis. More particularly, it is an object to provide such compositions that are highly homogeneous and which rapidly de-emulsify upon application to skin and that do not tend to re-emulsify, so as to ensure a substantially uniform, yet non-occlusive, layer of substantive protective barrier agent on the skin. It is a further object of the present invention to provide such compositions which are esthetically pleasing to the user. Another object of the invention is to provide such compositions that have a coefficient of friction that is sufficiently low so as to minimize the risk of skin abrasion or red-marking, to provide easier subsequent cleansing of the skin, and to improve the spreadability of other protective barrier agents that may be applied.

[0015] It is another object of the invention to provide a method of making such compositions.

[0016] Yet another object of the invention is to provide wipe products containing the composition, more particularly a wipe product that provides effective cleansing and that also leaves a substantive, highly protective residue on the skin. Another object of the invention is to provide a wipe product that is soft and non-irritating to the user.

#### Summary of the Invention

[0017] The present invention is directed to compositions for cleaning and leaving a protective residue on the skin of a person, the composition being especially

useful for reducing the risk of perineal dermatitis. The compositions contain water, a silicone oil and an emulsifier. Preferred compositions also include a water-soluble polyol, a pH-adjusting agent, an anti-microbial agent and/or a chelating agent. The components are combined to provide a stable, tactilely pleasant, non-irritating lotion that can rapidly de-emulsify upon application to the skin and remain de-emulsified to leave on the skin a substantially uniform protective layer of the silicone oil. The silicone oil tends to reduce the risk of perineal dermatitis, red-marking, and skin abrasion and tends to aid in the removal of body waste and in the application of other topical agents.

[0018] In preferred embodiments the silicone oil includes dimethicone and the emulsifier is a polymeric emulsifier, more preferably a carboxylic acid polymeric emulsifier, most preferably comprising an acrylates/C<sub>10</sub>-C<sub>30</sub> alkyl acrylate crosspolymer. The preferred anti-microbial agent includes a mixture of 1,3-bis(hydroxymethyl)-5,5-dimethylhydantoin and 3-iodo-2-propynyl butyl carbamate.

[0019] The present invention also relates to the use of the compositions in combination with a substrate to effect cleaning, treating, or other uses. In a preferred embodiment, the composition is pre-combined with the substrate to form a wipe product, e.g., disposable wipe products, to be used for such purposes at a later time. In a preferred embodiment, the wipe product includes a nonwoven substrate impregnated with the composition.

[0020] The preferred wipe products tend to be resistant to a wide range of microorganisms, such that the wipes have a good storage life. The wipe products also tend to be soft relative to wipe products that do not contain silicone oil, or wipe products that do not incorporate silicone oil substantially throughout the wipe product.

[0021] The invention also relates to methods of making the compositions. A preferred method involves adding the pH-adjusting agent at the end of the process of making the composition, or before an optional dilution step. The preferred method also uses a relatively low shear process of forming an emulsion of the silicone in the composition. The preferred method tends to provide highly homogeneous compositions that rapidly de-emulsify upon application to skin and that tend to remain de-emulsified so as to leave on the skin a substantially uniform layer of silicone oil.

#### Description of Preferred Embodiments

[0022] The compositions of the present invention are emulsions containing water, a protective barrier agent that includes a silicone oil, and an emulsifier. In preferred embodiments, the composition also contains at least one additional component selected from water-soluble polyols, pH-adjusting agents, anti-microbial agents and chelating agents. Additional ingredients, e.g., fragrance; skin soothing aids, moisteners, humectants and emollients; powders and the like may also be included

in the composition.

[0022] The water serves as a medium for carrying the protective barrier agent to the skin in an esthetically pleasant manner and at a suitable viscosity. In addition, the water aids in wetting of the substrate of wipe products incorporating the composition. The water may be deionized or tap water. Tap water is economically preferred. However, it may be preferred to use deionized water to minimize interference with emulsification due to trace metals and other trace compounds that may be found in tap water, or to otherwise provide control in manufacturing of the composition. The compositions of the present invention generally contain, at least 90% water, and up to 99.5% water, by weight of the composition. Particularly preferred compositions contain from 91% to 99.5% water, by weight of the composition.

[0023] The silicone oil is the primary protective barrier agent in the composition. The silicone tends to provide a protective barrier against body waste irritants while at the same time allowing normal transepidermal moisture loss such that the skin is not excessively hydrated. In addition, the silicone oil provides emolliency, lubricates the skin surface and tends to release soil to thereby facilitate skin cleaning. The silicone oil tends to impart less tack than other emollients that have been used in personal cleansing compositions, e.g., animal oils such as lanolin or petroleum based oils such as petrolatum and mineral oil. The silicone also imparts a feeling of silkiness, smoothness and softness to the user's skin, and tends to soften wipe products incorporating the composition.

[0024] Silicone oils that are useful herein are those that can be stably emulsified. Preferred silicone oils are those that impart a tactile impression of softness and smoothness, and which do not impart an excessive tactile perception of greasiness, oiliness, or coating, when incorporated into the composition. Non-volatile silicone oils are preferred over volatile silicone oils. Non-volatile silicones tend to provide wipe products that remain stable when exposed to the environment, tend to provide a lasting tactile impression, and tend to form a stable oil layer on the skin. Mixtures of silicones can be used. For example, volatile silicones may be used in combination with non-volatile silicones to impart desired esthetic properties, as long as the composition contains sufficient non-volatile silicone to provide a skin barrier layer that is effective for a given application.

[0025] Exemplary silicone oils that are suitable for use herein include dimethicone (alternatively referred to as linear polydimethylsiloxane polymer, dimethyl silcone and the like), substituted linear dimethicones, cyclomethicone, dimethiconol, trimethylsiloxysilicate, and mixtures thereof. Such silicones are commercially available, for example, from the Dow Corning Company of Midland, MI under the trade names Dow Corning 200 fluid (dimethicone), Dow Corning 1401 fluid (cyclomethicone and dimethiconol), Dow Corning 593 fluid (dimethicone and trimethylsiloxysilicate), and Dow Corning

2503 fluid (stearyl dimethicone). These and other silicone oils that may be suitable for use herein are described in the technical brochure numbered 24-414C-93 and entitled "Shaping Solutions for Personal Care,"

5 Dow Corning Corporation, Midland, MI, 1993.

[0026] In a preferred embodiment, the silicone oil is a linear dimethicone or mixture of linear dimethicones, more preferably a linear dimethicone or mixture thereof having a viscosity in the range of 50 to 1,000 mm<sup>2</sup>/s (centistokes) Exemplary dimethicones are available from Dow Corning under the trade names Dow Corning 200 Fluid. In a particularly preferred embodiment the silicone oil is the Dow Corning 200 Fluid having a viscosity of 350 mm<sup>2</sup>/s (centistokes). It has been found that this silicone oil provides a protective barrier without imparting an excessively greasy, oily, or tacky feeling to the composition when incorporated in the particularly preferred amounts.

[0027] Particularly preferred compositions contain 20 from 0.5% to 2.5%, most preferably from 1% to 2.5% silicone oil, based on the weight of the composition. Compositions containing the latter silicone content tend to provide a particularly suitable balance of skin protection and esthetic properties.

[0028] The composition also includes an emulsifier such as are known in the art of forming oil-in-water emulsions. The emulsifier is preferably a polymeric emulsifier. The polymeric emulsifier is capable of primary emulsification of the composition, and of rapidly de-emulsifying upon application of the composition to the skin to form a silicone oil film on the skin. In addition, the polymeric emulsifier does not tend to re-emulsify once the composition is applied to the skin. This is particularly important where the composition is to be used to clean or treat the perineal region, in which region repeated insults of urine can occur between changes of the diaper or other incontinence device. Since the composition does not re-emulsify to a significant extent, the silicone oil tends to remain on the skin in the form of a protective barrier layer, rather than being washed away by urine or other body fluids.

[0029] The emulsifier is employed in an amount effective to emulsify the silicone oil and other non-water-soluble oils that may be present in the composition (hereinafter alternatively referred to as "an effective amount"), typically an amount ranging from 0.05% to 1.0%, preferably from 0.05% to 0.5%, based on the weight of the composition. Particularly preferred compositions of the present invention contain from about 45 0.1% to 0.5%, more preferably from 0.1% to 0.3%, most preferably from 0.1 to 0.2% emulsifier, based on the weight of the composition. Mixtures of emulsifiers may be used.

[0030] Polymeric emulsifiers that are suitable for use herein include, but are not limited to carboxylic acid polymers which are crosslinked compounds containing one or more monomers derived from acrylic acid, substituted acrylic acids, and salts and esters of these acrylic acids

and the substituted acrylic acids, wherein the crosslinking agent contains two or more carbon-carbon double bonds and is derived from a polyhydric alcohol. The preferred carboxylic acid polymers are of two general types. Combinations of these two types of polymers are also useful herein.

[0031] The first type of preferred carboxylic acid polymer is a crosslinked homopolymer of an acrylic acid monomer or derivative thereof (e.g., wherein the acrylic acid has substituents on the two and three carbon positions independently selected from the group consisting of C<sub>1-4</sub> alkyl, -CN, -COOH, and mixtures thereof). The monomers are preferably selected from the group consisting of acrylic acid, methacrylic acid, ethacrylic acid, and mixtures thereof, with acrylic acid being most preferred.

[0032] The second type of preferred carboxylic acid polymer is a crosslinked copolymer having (i) a first monomer selected from the group consisting of an acrylic acid monomer or derivative thereof (as just described in the previous paragraph), a short chain alcohol (i.e., C<sub>1-4</sub>) acrylate ester monomer or derivative thereof (e.g., wherein the acrylic acid portion of the ester has substituents on the two and three carbon positions independently selected from the group consisting of C<sub>1-4</sub> alkyl, -CN, -COOH, and mixtures thereof), and mixtures thereof; and (ii) a second monomer which is a long chain alcohol (i.e., C<sub>8-40</sub>) acrylate ester monomer or derivative thereof (e.g., wherein the acrylic acid portion of the ester has substituents on the two and three carbon positions independently selected from the group consisting of C<sub>1-4</sub> alkyl, -CN, -COOH, and mixtures thereof). The acrylic acid monomer or derivative thereof is preferably selected from the group consisting of acrylic acid, methacrylic acid, ethacrylic acid, and mixtures thereof, with acrylic acid, methacrylic acid, and mixtures thereof being most preferred. The short chain alcohol acrylate ester monomer or derivative thereof is preferably selected from the group consisting of C<sub>1-4</sub> alcohol acrylate esters, C<sub>1-4</sub> alcohol methacrylate esters, C<sub>1-4</sub> alcohol ethacrylate esters, and mixtures thereof, with the C<sub>1-4</sub> alcohol acrylate esters, C<sub>1-4</sub> alcohol methacrylate esters, and mixtures thereof, being most preferred. The long chain alcohol acrylate ester monomer is selected from C<sub>8-40</sub> alkyl acrylate esters, with C<sub>10-30</sub> alkyl acrylate esters being preferred.

[0033] The crosslinking agent in both of the first and second types of preferred carboxylic acid polymers is a polyalkenyl polyether of a polyhydric alcohol containing more than one alkenyl ether group per molecule, wherein the parent polyhydric alcohol contains at least 3 carbon atoms and at least 3 hydroxyl groups. Preferred crosslinkers are those selected from the group consisting of allyl ethers of sucrose and allyl ethers of pentaerythritol, and mixtures thereof.

[0034] The carboxylic acid polymers useful in the present invention are more fully described in U.S. Patent No. 5,087,445, to Haffey et al., issued February 11,

1992; U.S. Patent No. 4,509,949, to Huang et al., issued April 5, 1985; U.S. Patent No. 2,798,053, to Brown, issued July 2, 1957; See also, CTFA International Cosmetic Ingredient Dictionary, fourth edition, 1991, pp. 12 and 80.

[0035] Examples of commercially available carboxylic acid polymers of the first type useful herein include the carbomers, which are homopolymers of acrylic acid crosslinked with allyl ethers of sucrose or pentaerythritol. The carbomers are available as the Carbopol® 900 series from the B. F. Goodrich Company of Cleveland, OH. Examples of commercially available carboxylic acid copolymers of the second type useful herein include copolymers of C<sub>10-30</sub> alkyl acrylates with one or more monomers of acrylic acid, methacrylic acid, or one of their short chain (i.e., C<sub>1-4</sub> alcohol) esters, wherein the crosslinking agent is an allyl ether of sucrose or pentaerythritol. These copolymers are known as acrylates/C<sub>10-30</sub> alkyl acrylate crosspolymers and are commercially available as Carbopol® 1342, Pemulen® TR-1, and Pemulen® TR-2, from B.F. Goodrich. In other words, examples of carboxylic acid polymeric emulsifiers useful herein are those selected from the group consisting of carbomers, acrylates/C<sub>10-C30</sub> alkyl acrylate crosspolymers, and mixtures thereof.

[0036] The acrylates/C<sub>10-C30</sub> alkyl acrylate crosspolymers are particularly preferred for use in the present invention. These emulsifiers can be generally described as hydrophobically modified hydrophilic polymers that tend to both emulsify oils in water and to stabilize the finished emulsion. They are predominantly high molecular weight polyacrylic acid based polymers having a small lipophilic portion and a large hydrophilic portion. These crosspolymers tend to provide improved oil in water emulsification relative to other known polymeric emulsifiers, and may offer the additional advantage of obviating the need for a buffer.

[0037] The Pemulen® emulsifiers are most preferred in the compositions of the present invention. The Pemulen® emulsifiers have a relatively high level of hydrophobicity and thus tend to form emulsions wherein the silicone oil droplets are highly stabilized against coalescence and creaming. In addition, the Pemulen® emulsifiers, and particularly Pemulen® TR-2, tend to enable lower viscosities. A relatively low viscosity is preferred for the personal cleansing wipe products of the present invention to ensure sufficient impregnation of the wipe product, for cleansing efficiency, and to provide a positive tactile impression. At the same time, compositions containing the Pemulen® emulsifiers tend to remain substantially uniformly distributed in the wipe product, i.e., settling of the composition does not occur to a significant extent. The Pemulen® emulsifiers and their use in personal care compositions are described in more detail in the technical brochure, "Introducing the New, Universal Pemulen® Polymeric Emulsifiers," B.F. Goodrich Company, April, 1994, and in "Pemulen® Polymeric Emulsifiers: What They Are, How They Work," R. Dod-

well, R. Lockhead, W. Hemmeker.

[0038] Additional emulsifiers that are useful herein are disclosed in the above referenced U.S. Patent 5,043,155 issued to Puchalski et al.

[0039] In preferred embodiments, the composition also contains one or more components selected from water-soluble polyols, pH-adjusting agents, anti-microbial agents and chelating agents.

[0040] Water-soluble (which includes water-miscible) polyols are polyols that are able to uniformly dissolve or disperse in water. The water-soluble polyol may serve several purposes in the composition. For example, the polyol may function as a skin moisturizer, humectant, or emollient. The polyol may additionally or alternatively potentiate the anti-bacterial agent. The polyol may be used as a solvent for one or more components of the composition.

[0041] Water-soluble polyols that are suitable for use herein include water-soluble alkylene polyols and water-soluble analogs of such polyols. Water-soluble analogs of these polyols include water-soluble esters of alkylene polyols. Non-limiting examples of water-soluble polyols suitable for use herein include ethylene glycol, propylene glycol, butylene glycol, diethylene glycols, triethylene glycols, other water-soluble polyethylene glycols, water-soluble polypropylene glycols, hexylene glycol, glycerol, polyoxyethylene sorbitol, 1,2,4- butane triol, 1,2,6-hexane triol, sorbitol and mixtures thereof. Propylene glycol is an economically preferred polyol. Butylene glycol and hexylene glycol, and particularly hexylene glycol, tend to potentiate the anti-microbial agent and are therefore preferred to provide a higher level of protection against the growth of microorganisms. Therefore, these glycols, and particularly hexylene glycol, are preferred for providing greater storage stability to the composition and wipe products containing the composition. These glycols may be particularly preferred where the wipes are formed from a porous substrate, e.g., a nonwoven.

[0042] The water-soluble polyol is employed in an amount effective to provide the desired function or functions, e.g., as a skin moisturizer, humectant and/or emollient, as a solvent for other components of the composition, or to potentiate the anti-bacterial agent (herein alternatively referred to as "an effective amount"). Typically, the water-soluble polyol will be used in an amount of from 0.5 to 3%, preferably from 0.5 to 2%, more preferably from 0.5 to 1%, based on the weight of the composition. Mixtures of such agents may be used.

[0043] It is generally desired in personal cleansing or treating compositions to adjust the pH of the composition to that or near that of skin. Therefore, the pH will typically be adjusted as may be necessary to provide the composition with a pH of from 4 to 7, more preferably from 4.5 to 6.5. The pH can be adjusted by adding one or more pH-adjusting agents in an amount effective to provide such pH values (herein alternatively referred to as "an effective amount"). Agents that may be used to

adjust the pH of the compositions herein include organic and inorganic acids and bases.

[0044] For the preferred compositions of the present invention, which employ a carboxylic acid polymeric emulsifier, the composition in the absence of a pH-adjusting agent tends to be more acidic than desired. Therefore, a basic pH-adjusting agent will typically be used to bring the composition to the desired pH. Basic pH-adjusting agents include organic amine bases, preferably amines that are relatively non-irritating and which have a relatively low equivalent weight, for example, triethanolamine, trimethylamine, tromethamine, aminomethyl propanol and tetrahydroxy ethylene diamine. Higher grade versions (i.e., at least 99% pure) of organic amine bases are preferred. Inorganic bases, including alkali metal salts such as NaOH, can also be used. The organic amines will typically be preferred since they have a lower risk of irritation, and their titration is more readily controlled, relative to inorganic bases. Other pH-adjusting agents are described in the above referenced U.S. Patent 5,043,155.

[0045] The amount of the pH-adjusting agent that is employed depends on the equivalent weight of the pH-adjusting agent and the desired pH. Typically, the pH-adjusting agent is used in an amount of from 0.01 to 0.5 weight % of the composition. Preferred compositions of the present invention include from 0.05 to 0.2 weight %, typically 0.1 to 0.2 weight % pH-adjusting agent.

[0046] Anti-microbial agents may function in one or more ways to improve the shelf life of the composition and products incorporating the composition. For example, the anti-microbial may be a preservative, an anti-bacterial agent, an anti-fungal agent, or a combination thereof. The anti-microbial agent is used as may be required in an amount which is effective to provide a suitable shelf life (storage stability, i.e., microorganisms do not grow to a significant extent) (herein alternatively referred to as "an effective amount"). Useful products will typically have a shelf life of at least 1 year under storage conditions of about 75°F and 50% Relative Humidity (measured in accordance with United States Pharmacopeia test entitled "Microbial Test, Antimicrobial Preservative - Effectiveness"). The anti-microbial agent is typically used in an amount of from 0.05% to about 0.5% based on the weight of the composition. Preferred compositions of the present invention employ from 0.1 to 0.3 weight % anti-microbial agent. One or more anti-microbial agents may be employed.

[0047] The anti-microbial agent is preferably substantially water-soluble and insoluble in the silicone oil. Anti-microbial agents that are suitable for use herein include, but are not limited to, those described in the above referenced U.S. Patent 5,043,155 issued to Puchalski et al., and in U.S. Patent 4,844,891 issued to Rosen et al. on July 4, 1989. A preferred anti-microbial agent is available from Lonza, Inc. of Fairlawn, NJ, under the trade name Glydant Plus®. Glydant Plus® comprises a mixture of 1,3-bis(hydroxymethyl)-5,5-dimethylhydantoin (i.

e., DMDMH) and 3-iodo-2-propynyl butyl carbamate (the mixture may also comprise a minor amount of hydroxymethyl-5,5-dimethylhydantoin (i.e., DMH)). It has been found that the Glydant Plus® is highly effective in preventing the growth of a wide variety of microbes, and is advantageously efficacious against the growth of fungi. This tends to be particularly important where the wipe product contains a porous substrate, for example, non-woven substrates. The Glydant Plus® tends to provide wipe products having exceptional storage stability under a variety of storage conditions, including storage at or below the temperature of freezing. Alternatively preferred anti-microbial agents are described in the above-referenced U.S. Patent 4,844,891.

[0048] The composition preferably contains one or more chelating agents. The chelating agent tends to bind metals (e.g., calcium ions, magnesium ions) that may be present in the composition so as to enhance the efficiency of the emulsifier and the anti-microbial agent. Thus, the chelating agent may be considered to provide a level of anti-microbial activity to function, for example, as a preservative. The chelating agent may be used in an amount that is effective to bind the aforementioned metals (hereinafter alternatively referred to as an "effective amount"), typically an amount ranging from about 0.01 % to about 0.2 weight % of the composition. Particularly preferred compositions include from about 0.05% to about 0.2%, more preferably from about 0.05% to about 0.15% chelating agent, based on the weight of the composition. Chelating agents and their use in personal cleansing compositions are well known in the art. Exemplary chelating agents are disclosed in the above referenced U.S. Patent 5,043,155 and include disodium EDTA, trisodium EDTA, and tetrasodium EDTA.

[0049] The composition may optionally include other ingredients, e.g., fragrance; skin soothing aids such as panthenol, bisabolol, green tea extract, kola extract, ichthammol, stearyl glycyrrhetinate, ammonium glycyrrhinate, Vitamin E (tocopherol or tocopherol acetate), and aloe; skin moisteners, humectants, or emollients other than those previously described; powders and the like.

[0050] Preferred compositions of the present invention will contain from 91 to 99.5 weight % water and 0.5 to less than 3 weight % silicone oil, more preferably 0.5 to 2.5 weight % silicone oil; most preferably 1 to 2.5 weight % silicone oil. Such compositions will contain an effective amount of emulsifier as previously described. The compositions may also contain one or more agents selected from anti-microbial agents, water-soluble polyols, pH-adjusting agents, and chelating agents as previously described. These agents may be used in an effective amount as previously described.

[0051] The composition preferably contains from 91 to 99.5 weight % water, from 0.05 to 1 weight % emulsifier, and from 0.5 to less than 3 weight % silicone oil, more preferably 0.5 to 2.5 weight % silicone oil, most preferably 1 to 2.5 weight % silicone oil.

[0052] Particularly preferred compositions will contain

an anti-microbial agent, a water-soluble polyol, a pH-adjusting agent, and a chelating agent in the amounts previously described. Preferred compositions of this type contain from about 91 to 99 weight % water, from 5

0.5 to less than 3 weight % silicone oil, from 0.05 to 1 weight % emulsifier, from about 0.05 to 0.5 weight % anti-microbial agent, from 0.5 to 3 weight% water-soluble polyol, from 0.01 to 0.5 pH-adjusting agent, and from 0.01 to 0.2 weight % chelating agent. Compositions of

10 this type more preferably contain from about 0.5 to about 2.5, most preferably from 1 to about 2.5, weight % silicone, the amounts of the other non-aqueous ingredients and water being within the ranges stated in this paragraph and balancing the composition to 100 weight %.

15 The water content of these latter compositions may range from 92 to 99% and, respectively, from about 92 to 98.5%.

[0053] Exemplary preferred compositions of the present invention thus include:

20 (A) from 92 to 99 weight % water, from 0.5 to less than 3 weight % silicone oil, from 0.1 to 0.5 weight % emulsifier, from 0.05 to 0.5 weight % anti-microbial agent, from 0.5 to 3 weight% water-soluble polyol, from 0.01 to 0.5 pH-adjusting agent, and from 0.01 to 0.2 weight % chelating agent;

25 (B) from about 94.5 to about 99 weight % water, from 0.5 to 2.5 weight % silicone oil, from 0.1 to about 0.3 weight % anti-microbial agent, from 0.5 to 2 weight% water-soluble polyol, from 0.05 to 0.2 pH-adjusting agent, and from 0.05 to 0.2 weight % chelating agent; and

30 (C) from 95 to 98.5 weight % water, from 1 to 2.5 weight % silicone oil, from 0.1 to 0.2 weight % emulsifier, from 0.1 to 0.3 weight % anti-microbial agent, from 0.5 to 1 weight% water-soluble polyol, from 0.1 to 0.2 pH-adjusting agent, and from 0.05 to about 0.15 weight % chelating agent.

35 [0054] In the foregoing compositions, the emulsifier is preferably a polymeric emulsifier, more preferably a carboxylic acid polymeric emulsifier, most preferably an acrylates/C<sub>10</sub>-C<sub>30</sub> alkyl acrylate/cross polymeric emulsifier. A particularly preferred emulsifier is Pemulen®

40 TR-2. The preferred silicone is dimethicone more preferably dimethicone havin a viscosity of from 50 to 1,000 mm<sup>2</sup>/s (centistokes), most preferably a viscosity of 350 mm<sup>2</sup>/s (centistokes) centistokes. The preferred anti-microbial agent comprises a mixture of 1,3-bis(hydroxymethyl)-5,5-dimethylhydantoin and 3-iodo-2-propynyl butyl carbamate such as previously described.

45 [0055] The compositions may be prepared by oil-in-water emulsion techniques such as are known or become known in the art. In general, the process involves 50 the steps of preparing a mixture of the ingredients of the composition and subjecting the mixture to conditions to cause the formation of a homogeneous and stable oil-in-water emulsion (a suspension of the silicone oil in the

water and water-soluble materials is formed). Homogeneity is indicated by a composition which is substantially smooth, lump-free and uniform in appearance. A stable emulsion remains homogeneous over a given period which is determined by the required shelf life of the composition.

[0056] The mixture may be formed in one step by addition and mixing of each of the ingredients. Alternatively, less than all of the ingredients may be pre-combined for subsequent combination with other ingredients or other pre-combined ingredients to form the mixture. For example, the anti-microbial agent may be pre-mixed with a portion of the water, water-soluble polyol, or a mixture thereof.

[0057] In a preferred embodiment, at least a portion of the water, the emulsifier, the silicone oil, and the optional water-soluble polyol, anti-microbial agent and chelating agent are first combined and subjected to conditions to form the emulsion. The pH-adjusting agent is then added and mixed into the emulsion. Where the resultant emulsion has been prepared with less than the finally desired level of water, the emulsion may thereafter be diluted to form the composition of the invention. When this process is employed, the composition tends to be particularly homogeneous. Such compositions tend to be more uniformly distributed on and/or absorbed by a substrate to be used in the wipe products described herein. In addition, the film of silicone oil that is subsequently formed on the skin tends to be more uniform to thereby provide a more effective protective barrier layer. In addition, this method tends to reduce energy needs for manufacturing the composition.

[0058] The mixture may contain each of the ingredients in the total amounts intended. Alternatively, the mixture may contain less than the total of each ingredient, typically less than the entire amount of water, such that a concentrated emulsion is formed. The concentrate will typically be designed to provide both a volume that is preferred for storage and/or shipping, and a workable viscosity. For example, a 5-fold concentrate may be formed. The concentrated emulsion may then be diluted by adding the balance of the ingredients to form the composition of the present invention. A suitable method of forming an emulsion concentrate is described in the above-referenced U.S. Patent 5,043,155. Although the use of a concentrated emulsion technique may be economically preferred, it has been found that such a technique is not required to obtain the compositions of the present invention.

[0059] Equipment suitable for forming the mixtures and emulsion may be selected from those known in the art or which become known in the art. For example, suitable apparatus include dual propeller blade mixers. A turbine mixer and an in-line homogenizer using tandem rotor-stators, such as described in the above-referenced U.S. Patent 5,043,155, may also be used. A single shaft motor equipped with two propeller blades has been found to be suitable for preparing the compositions of

the present invention. In a preferred configuration, the shaft extends substantially through the depth of the mixing vessel and has a first blade that is positioned as near the bottom of the vessel as is possible and a second

5 shaft positioned within approximately the lower half preferably the lower fourth, of the vessel, and more preferably within about 0.305 m (foot) of the first blade. The first blade preferably has a diameter approaching that of the vessel diameter, more preferably as near to that of the vessel as possible, while the second blade may be the same size or substantially smaller. The mixer is suitably rated to drive a free shaft at a speed of from 1,000 rpm to 15,000 rpm. Preferably, the motor is rated to drive a free shaft at a speed of from 1000 to at least 6000 rpm.

[0060] To form the emulsion, the mixture is typically mixed for a period of from 5 to 60 minutes, with the motor speed set to drive a free shaft at a rate of from 1,000 rpm to 15,000 rpm, preferably 1000 rpm to 6000 rpm. In 10 a particularly preferred embodiment, the mixture is mixed for a period of from 5 to 30 minutes, with the motor speed set to drive a free shaft at a rate of from 1000 rpm to 3000 rpm. As will be understood by the skilled artisan, care should be taken to avoid subjecting the mixture to 15 excessive shear, which may interfere with emulsification.

[0061] The resultant emulsion containing the ingredients in their total amounts has a preferred viscosity at room temperature (i.e., 20°-25°C) in the range of from 20 10 to 200 mPas (centipoise), more preferably from 15 to 150 mPas (centipoise), most preferably from 20 to 100 mPas (centipoise). The viscosity can be determined using a Brookfield RVT viscometer equipped with a #1 spindle at a speed of 20 rpm according to the readily

25 available and commonly used procedures for the Brookfield viscometer or an equivalent apparatus and method. The emulsion tends to remain stable for a period in excess of one year at room temperature, or one month at 30 45°C. Instability is indicated by a significant variation, 35 typically a significant decrease, in viscosity. Instability is also indicated by the appearance of layers in the depth of the composition, when viewed from a horizontal perspective in a transparent container with the naked eye.

[0062] The compositions of the present invention are 40 particularly useful for personal cleansing and/or skin treating applications. The compositions can be applied directly to the skin, for example, by spraying, dripping, smoothing, rubbing, massaging and the like. Additionally or alternatively, the compositions can be applied

45 with the use of a suitable applicator comprising a substrate material for holding the composition. Non-limiting examples of substrate materials are sponges, foams, nonwovens, films and the like. Thus, the compositions of the present invention are particularly suitable for use 50 in combination with a substrate to effect personal cleansing, skin treating, or other personal care uses. In a preferred embodiment, the composition is pre-combined with the substrate to form a wipe product, e.g., 55

disposable wipe products, to be used for such purposes at a later time. As used herein, "wipe product" means a substrate and a composition of the present invention which are pre-combined for later use. Disposable wipe products are those which are intended to be discarded after a single use (i.e., the original wipe product in its whole is not intended to be laundered or otherwise restored or reused as a wipe product, although certain materials or all of the wipe product may be recycled, reused, or composted). The compositions and wipe products are well-suited for use in cleaning and/or treating the perineal area of infants or other incontinent individuals (e.g., for use as infant wipes or incontinent adult wipes). However, it is to be understood that the compositions and wipe products of the present invention are useful in other applications, including but not limited to facial and hand cleansing and/or treating.

[0063] Suitable wipe substrates include nonwovens, films, foams, sponges, and the like. Preferred wipe substrates comprise a porous material which is capable of holding the composition within the pores of the substrate. Therefore, preferred substrates include nonwovens, foams, sponges and the like. For infant and incontinent adult wipe products, the substrate will preferably be a nonwoven. Nonwoven substrates used for the wipe product can be formed of cellulosic fibrous materials, synthetic polymeric fibrous materials, or a combination thereof (e.g., coform). For example, the nonwoven may contain from 1% to 99% by weight cellulosic fiber and, respectively, from 99% to 1% by weight synthetic polymeric fibers. Non-limiting examples of such materials include paper tissue, paper toweling, and nonwovens formed from rayon, polyolefins, polyester fibrous material or a combination of such materials with cellulosic fibers. The nonwovens may be air-laid, wet-laid, spun-laid, meltblown, or carded. The nonwoven may include one or more layers of fibrous material; e.g. a laminate of fibrous material. The separate layers may be formed of similar or dissimilar materials. The nonwoven may be treated, for example, to join the fibers of the nonwoven or to enhance the strength of the nonwoven. Such treatment may involve hydroentanglement, thermal bonding, or treatment with a binder.

[0064] Cellulosic nonwovens, particularly nonwovens wherein the fibrous material consists essentially of cellulosic products, are economically and environmentally preferred. Cellulosic nonwovens that are especially suitable for use in the present invention are described in U.S. Patent 3,905,863 issued to Ayers on September 16, 1975; U.S. Patent 3,974,025 issued to Ayers on August 10, 1976; and U.S. Patent 4,191,609 issued to Trokhan on March 4, 1980.

[0065] Techniques for combining wipe substrates with a cleansing or treating composition, and for their packaging are well known in the art and are applicable to the present invention. In general, the wipe substrate is combined with the composition by one or more techniques involving coating, immersing, dipping, spraying, extrud-

ing, and the like. In general, the wipes are combined with an amount of the composition sufficient to provide good effective cleansing. It is often important to employ a loading that provides an acceptable tactile impression (e.g., sufficient but not excessive wetness, not excessively greasy or oily). Thus, the wipe substrates are typically combined with the composition in an amount of from about 2 to about 8 times, preferably about 3 to about 5 times the dry weight of the substrate. For example, a suitable incontinent adult wipe for use in cleansing the perineal area, which contains a cellulosic nonwoven, may contain the composition in an amount of about 3 times the dry weight of the nonwoven.

[0066] The following non-limiting examples are representative of the present invention.

#### Examples

(a) Preparation of a composition according to the present invention:

[0067] An emulsion containing 96.4% water, 2% silicone oil, 0.15% carboxylic acid polymeric emulsifier, 1% water soluble alkylene polyol, 0.1% chelating agent, 0.2% anti-microbial agent, 0.15% organic base pH-adjusting agent, and fragrance is prepared in the following manner.

[0068] A standard size 208.2 l (55 gallon) covered cylindrical drum fitted with a single shaft having dual propeller blades, driven by a motor rated at 1750 rpm, is used to prepare the emulsion. The shaft extends substantially through the depth of the drum (1.2192 m 4 feet) and has a first blade that is positioned near the bottom of the drum and a second shaft positioned about 1 foot above the first blade. The first blade has a diameter approaching that of the drum diameter (0.6096 m 2 feet), and the second blade has a diameter of 0.305 m (1 foot).

[0069] The drum is charged with 153.2 l (40.48 gallons) of tap water. Agitation of the water is begun by operating the motor at its maximum rated speed. Agitation at this speed is continued throughout the entire process. 0.24 kg (0.52 lbs). Pemulen® TR-2 is added slowly, to allow mixing of the emulsifier with the water sufficient to disperse or avoid the formation of lumps of the emulsifier. The following components are then added in the order stated 0.16 kg (0.35 lbs) tetrasodium EDTA; 1.58 kg (3.49 lbs) propylene glycol 3.16 kg (6.97 lbs) dimethicone (Dow Corning 200 Fluid, 350 cs) 0.32 kg (0.70 lbs) Glydant Plus® 0.004 kg (0.01) lbs of fragrance. Each of the foregoing ingredients are individually mixed into the water until they are well blended into the resultant mixture, typically by agitating for a period of about 1 minute between addition of the individual ingredients, and for a period of about 5-10 minutes once all the ingredients are added to the vessel.

[0070] 0.24 kg (0.52 lbs) triethanolamine is then added and agitation is continued for a period of about 15-20 minutes, or until the mixture is well blended. The pH of

the composition is about 6.5. Lower or higher pH compositions can be prepared in a similar manner by adding more or less triethanolamine, respectively. For example, a composition having a pH of from 5-6 can be prepared by adding a lower level of triethanolamine. The resultant emulsion has a viscosity of 120 mPas (centipoise) (Brookfield LVT, #3 spindle, 30 rpm 15.5°C (60°F) measured upon stabilization of viscometer reading after approximately 15 seconds of spindle rotation).

(b) Preparation of a disposable wipe product containing composition according to the invention:

[0071] A wipe composed of a two -ply cellulose substrate of 100% NSK fiber, having a Basis Weight of 11.8 kg (26 lbs) per ply and a Caliper of 20 mils per ply, are laminated together under pressure with an adhesive, and rolled into a continuous web roll. Suitable adhesives have a wet strength that is sufficient for the plies to remain substantially bonded in use. The web roll is slit to achieve the desired finished wipe width (e.g 29.2 cm (11.5") in the unfolded configuration), and z-folded so that the machine direction edges overlap about 7cm (0.5").

[0072] The resultant slit and folded webs are then impregnated with the composition prepared in (a) by passing the individual webs over the top of individual manifolds having holes through which the composition is pumped under pressure onto the moving web. The composition is pumped so as to provide a loading of about 15.5 grams of composition per finished wipe.

[0073] Following impregnation, the webs cut to the desired finished wipe length (e.g., about 8.5").

### Claims

1. A wipe product comprising a substrate and an emulsion composition, the wipe product characterized in that the composition comprises:

- (a) at least 90% by weight water;
- (b) 0.5% to 2.5%, by weight silicone oil; and
- (c) an emulsifier in an amount effective to emulsify said oil in said water; said silicone oil preferably comprising a dimethicone polymer having a viscosity of from 50 to 1000 mm<sup>2</sup>/s (centistokes) more preferably 350 mm<sup>2</sup>/s (centistokes); and said emulsifier preferably being a polymeric emulsifier, more preferably a carboxylic acid polymeric emulsifier, most preferably an acrylates/C10-C30 alkyl acrylate crosspolymer.

2. The wipe product of Claim 1 further comprising an effective amount of an agent selected from the group consisting of:

5 (a) anti-microbial agents, preferably comprising a mixture of 1,3-bis(hydroxymethyl)-5,5-dimethylhydantoin and 3-iodo-2-propynyl butyl carbamate;

(b) pH-adjusting agents, preferably comprising an organic basic amine;

(c) chelating agents;

(d) water-soluble polyols, preferably selected from the group consisting of water-soluble alkylene polyols, water-soluble esters of alkylene polyols, and mixtures thereof; more preferably comprising a C<sub>3</sub>-C<sub>8</sub> alkylene glycol; and

(e) mixtures thereof.

15 3. A wipe product comprising a substrate and an emulsion composition, the wipe product characterized in that the composition comprises:

20 (a) 90 to 99.5 weight %, preferably 91 to 99 weight % water;

(b) 0.5% to 2.5 weight %, more preferably 1% to 2.5 weight % silicone oil;

(c) a carboxylic acid polymeric emulsifier comprising an acrylates/C10-C30 alkyl acrylate crosspolymer in an amount effective to emulsify said oil in said water, preferably 0.05 to 1 weight %; and

25 (d) an effective amount of an anti-microbial agent comprising a mixture of 1,3-bis(hydroxymethyl)-5,5-dimethylhydantoin and 3-iodo-2-propynyl butyl carbamate;

30 said silicone oil preferably comprising a dimethicone polymer having a viscosity of 50 to 1000 mm<sup>2</sup>/s (centistokes).

35 4. The wipe product of Claim 3 wherein said composition additionally comprises an effective amount of an agent selected from the group consisting of basic pH-adjusting agents, chelating agents, and mixtures thereof.

40 5. The wipe product of Claim 3 or 4 wherein said composition additionally comprises an effective amount of a water-soluble polyol selected from the group consisting of water-soluble alkylene polyols, water-soluble esters of alkylene polyols, and mixtures thereof; said composition preferably comprising 0.5 to 3 weight % of said water-soluble polyol; 0.05 to 0.5 weight % of said anti-microbial agent; 0.01 to 0.2 weight % of said chelating agent, and 0.01 to 0.5 weight % of said basic pH-adjusting agent.

45 6. The wipe product of any of Claims 1 - 5 wherein the substrate is a nonwoven, preferably comprising celulose fibers.

50

7. The wipe product of any of Claims 1 - 6 wherein the product comprises said composition in an amount of from 2 to 8 times the dry weight of said substrate.
8. An emulsion composition suitable for cleansing or treating the skin of a person, the composition characterized in that it comprises:
- (a) at least 90 weight %, preferably 91 to 99 weight % water; 10
  - (b) 0.5 to 2.5 weight % of a silicone oil;
  - (c) a carboxylic acid polymeric emulsifier comprising an acrylates/C10-C30 alkyl acrylate crosspolymer in an amount effective to emulsify said oil in said water, preferably 0.05 to 1 weight %; and 15
  - (d) an effective amount, preferably 0.05 to 0.5 weight %, of an anti-microbial agent comprising a mixture of 1,3-bis(hydroxymethyl)-5,5-dimethylhydantoin and 3-iodo-2-propynyl butyl carbamate. 20
9. The composition of Claim 8 additionally comprising:
- (e) an effective amount, preferably 0.5 to 3 weight %, of a water-soluble polyol selected from the group consisting of water-soluble alkylene polyols, water-soluble esters of alkylene polyols, and mixtures thereof; 25
  - (f) an effective amount, preferably 0.01 to 0.2 weight %, of a chelating agent, and
  - (g) an effective amount, preferably 0.01 to 0.5 weight %, of a basic pH-adjusting agent. 30
10. A method to produce the emulsion composition according to claim 8, wherein said composition is formed by one step addition and mixing of each of the ingredients. 35
11. A method according to claim 10, wherein said composition further comprises an antimicrobial agent, a chelating agent and a pH adjusting agent, wherein said method comprises the steps of first combining at least a portion of the water, said emulsifier, said silicone oil, said antimicrobial agent and said chelating agent to form an emulsion and then adding said pH adjusting agent. 40
12. A method according to claim 10, wherein said ingredients of said composition are mixed with the motor speed set to drive a free shaft at a rate of from 1000rpm to 6000rpm for from 5 to 60 minutes. 50
- Patentansprüche 55
1. Wischprodukt mit einem Substrat und einer Emulsionszusammensetzung, wobei das Wischprodukt dadurch gekennzeichnet ist, daß die Zusammensetzung umfaßt:
- (a) wenigstens 90 Gew.% Wasser;
  - (b) 0,5 Gew.% bis 2,5 Gew.% Siliconöl; und
  - (c) einen Emulgator in einer effektiven Menge, um das Öl in dem Wasser zu emulgieren; wobei das Siliconöl vorzugsweise ein Dimethiconpolymer umfaßt, das eine Viskosität von 50 bis 1000 mm<sup>2</sup>/s (Centistokes), vorzugsweise 350 mm<sup>2</sup>/s (Centistokes); und wobei der Emulgator vorzugsweise ein Polymeremulgator ist, vorzugsweise ein Carboxylsäure-Polymeremulgator, ganz bevorzugt ein Acrylat/C10-C30-Alkylacrylatkreuzpolymer.
2. Wischprodukt nach Anspruch 1, ferner mit einer effektiven Menge eines Mittels ausgewählt aus der Gruppe bestehend aus:
- (a) antimikrobielle Mittel, vorzugsweise mit einem Gemisch aus 1,3-bis(Hydroximethyl)-5,5-Dimethylhydantoin und 3-Iodid-2-Propynylbutylkarbamat;
  - (b) pH-Einstellmitteln, vorzugsweise mit einem organischen basischen Amin;
  - (c) chelatbildende Mittel;
  - (d) wasserlösliche Polyole, vorzugsweise ausgewählt aus der Gruppe bestehend aus wasserlöslichen Alkenpolyolen, wasserlöslichen Estern aus Alkenpolyolen und Mischungen daraus; vorzugsweise umfassend ein C<sub>3</sub>-C<sub>8</sub>-Alkenglykol; und
  - (e) Mischungen daraus.
3. Wischprodukt umfassend ein Substrat und eine Emulsionszusammensetzung, wobei das Wischprodukt dadurch gekennzeichnet ist, daß die Zusammensetzung umfaßt:
- (a) 90 bis 99,5 Gew.%, vorzugsweise 91 bis 99 Gew.% Wasser;
  - (b) 0,5 Gew.% bis 2,5 Gew.%, vorzugsweise 1 Gew.% bis 2,5 Gew.% Siliconöl;
  - (c) einen Carboxylsäure-Polymeremulgator mit einem Acrylat/C10-C30 Alkylacrylatkreuzpolymer in einer effektiven Menge, um das Öl in dem Wasser zu emulgieren, vorzugsweise 0,05 bis 1 Gew.%; und
  - (d) eine effektive Menge eines antimikrobiellen Mittels mit einem Gemisch aus 1,3-bis(hydroximethyl)-5,5-dimethylhydantoin und 3-Jodid-2-propynylbutylkarbamate;
- wobei das Siliconöl vorzugsweise ein Dimethiconpolymer mit einer Viskosität von 50 bis 1000 mm<sup>2</sup>/s (Centistokes) umfaßt.

4. Wischprodukt nach Anspruch 3, in welchem die Zusammensetzung zusätzlich umfaßt eine effektive Menge eines Mittels ausgewählt aus der Gruppe bestehend aus basischen pH-Einstellmitteln, chelatbildenden Mitteln und Mischungen daraus.
5. Wischprodukt nach Anspruch 3 oder 4, in welchem die Zusammensetzung zusätzlich umfaßt eine effektive Menge eines wasserlöslichen Polyols ausgewählt aus der Gruppe bestehend aus wasserlöslichen Alkenpolyolen, wasserlöslichen Estern von Alkenpolyolen und Mischungen daraus; wobei die Zusammensetzung vorzugsweise umfaßt 0,5 bis 3 Gew.% des wasserlöslichen Polyols; 0,05 bis 0,5 Gew.% des antimikrobiellen Mittels; 0,01 bis 0,2 Gew.% des chelatbildenden Mittels und 0,01 bis 0,5 Gew.% des basischen pH-Einstellmittels.
6. Wischprodukt nach einem der Ansprüche 1 - 5, in welchem das Substrat ein Vliesstoff ist, vorzugsweise mit Zellulosefasern.
7. Wischprodukt nach einem der Ansprüche 1 - 6, in welchem das Produkt die Zusammensetzung in einer Menge vom 2 bis 8-fachen des Trockengewichts des Substrats umfaßt.
8. Emulsionszusammensetzung geeignet zum Reinigen und Behandeln der Haut eines Menschen, wobei die Zusammensetzung dadurch gekennzeichnet ist, daß diese umfaßt:
- (a) wenigstens 90 Gew.%, vorzugsweise 91 bis 99 Gew.% Wasser;
  - (b) 0,5 bis 2,5 Gew.% eines Siliconöls;
  - (c) einen Carboxylsäure-Polymeremulgator umfassend ein Acrylat/C10-C30 Alkylacrylatkreuzpolymer in einer effektiven Menge, um das Öl in dem Wasser zu emulgieren, vorzugsweise 0,05 bis 1 Gew.%; und
  - (d) eine effektive Menge, vorzugsweise 0,05 bis 0,5 Gew.%, eines antimikrobiellen Mittels umfassend ein Gemisch aus 1,3-bis(hydroxymethyl)-5,5-dimethylhydantoin und 3-jodid-2-propynylbutylkarbamat.
9. Zusammensetzung nach Anspruch 8 zusätzlich umfassend:
- (e) eine effektive Menge, vorzugsweise 0,5 bis 3 Gew.%, eines wasserlöslichen Polyols ausgewählt aus der Gruppe bestehend aus wasserlöslichen Alkenpolyolen, wasserlöslichen Estern aus Alkenpolyolen und Mischungen daraus;
  - (f) eine effektive Menge, vorzugsweise 0,01 bis 0,2 Gew.%, eines chelatbildenden Mittels, und
  - (g) eine effektive Menge, vorzugsweise 0,01 bis 0,5 Gew.%, eines basischen pH-Einstellmittels.
10. Verfahren zum Herstellen der Emulsionszusammensetzung gemäß Anspruch 8, in welchem die Zusammensetzung in einem Schritt durch Zugabe und Mischen jedes der Inkredenzen gebildet wird.
11. Verfahren nach Anspruch 10, in welchem die Zusammensetzung ferner umfaßt ein antimikrobielles Mittel, ein chelatbildendes Mittel und ein pH-Einstellmittel, wobei das Verfahren die Schritte umfaßt, zuerst wenigstens eines Anteil Wasser, den Emulgator, das Siliconöl, das antimikrobielle Mittel und das chelatbildende Mittel zu kombinieren, um eine Emulsion zu bilden, und dann das pH-Einstellmittel hinzuzufügen.
12. Verfahren nach Anspruch 10, in welchem die Ingredienzen der Zusammensetzung gemischt werden, wobei die Motorgeschwindigkeit so eingestellt ist, daß diese eine freie Welle für 5 bis 60 Minuten mit einer Geschwindigkeit von 1000 rpm bis 6000 rpm antreibt.

#### Revendications

1. Lingette à essuyer comprenant un substrat et une composition en émulsion, la lingette à essuyer étant caractérisée en ce que la composition comprend:
  - (a) au moins 90% en poids d'eau;
  - (b) 0,5% à 2,5% en poids d'une huile de silicium; et
  - (c) un émulsifiant, en quantité efficace pour émulsionner ladite huile dans ladite eau; ladite huile de silicium comprenant de préférence un polymère de diméthicone ayant une viscosité de 50 à 1 000 mm<sup>2</sup>/s (centistokes), mieux encore de 350 mm<sup>2</sup>/s (centistokes), et ledit émulsifiant étant de préférence un émulsifiant polymère, mieux encore un émulsifiant polymère d'acide carboxylique, tout particulièrement un polymère réticulé alkyle en C<sub>10</sub>-C<sub>30</sub>-acrylates.
2. Lingette à essuyer selon la revendication 1, comprenant par ailleurs une quantité efficace d'un agent choisi dans le groupe constitué par:
  - (a) des agents antimicrobiens, comprenant de préférence un mélange de 1,3-bis(hydroxyméthyl)-5,5-diméthylhydantoïne et de butylcarbamate de 3-iodo-2-propynyle;
  - (b) des agents d'ajustement du pH, comprenant de préférence une amine basique organique;
  - (c) des agents chélatants;

- (d) des polyols solubles dans l'eau, choisis de préférence dans le groupe constitué par les alkylènepolyols solubles dans l'eau, les esters d'alkylènepolyols solubles dans l'eau, et leurs mélanges; mieux encore, comprenant un alkylène(en C<sub>3</sub>-C<sub>8</sub>)-glycol; et  
 (e) des mélanges de ceux-ci.
3. Lingette à essuyer comprenant un substrat et une composition en émulsion, la lingette à essuyer étant caractérisée en ce que la composition comprend:  
 (a) 90 à 99,5% en poids, de préférence 91 à 99% en poids d'eau;  
 (b) 0,5% à 2,5% en poids, mieux encore 1% à 2,5% en poids, d'une huile de silicone;  
 (c) un émulsifiant de type polymère d'acide carboxylique comprenant un polymère réticulé alkyle en C<sub>10</sub>-C<sub>30</sub>-acrylates, en quantité efficace pour émulsionner ladite huile dans ladite eau, de préférence à raison de 0,05 à 1% en poids; et  
 (d) une quantité efficace d'un agent antimicrobien comprenant un mélange de 1,3-bis(hydroxyméthyl)-5,5-diméthylhydantoïne et de butylcarbamate de 3-iodo-2-propynyle;
- ladite huile de silicone comprenant de préférence un polymère de diméthicone ayant une viscosité de 50 à 1 000 mm<sup>2</sup>/s (centistokes).
4. Lingette à essuyer selon la revendication 3, dans laquelle ladite composition comprend en outre une quantité efficace d'un agent choisi dans le groupe constitué par les agents d'ajustement du pH basiques, les agents chélatants, et leurs mélanges.
5. Lingette à essuyer selon la revendication 3 ou 4, dans laquelle ladite composition comprend en outre une quantité efficace d'un polyol soluble dans l'eau choisi dans le groupe constitué par les alkylènepolyols solubles dans l'eau, les esters d'alkylènepolyols solubles dans l'eau, et leurs mélanges; ladite composition comprenant de préférence 0,5 à 3% en poids dudit polyol soluble dans l'eau; 0,05 à 0,5% en poids dudit agent antimicrobien; 0,01 à 0,2% en poids dudit agent chélatant; et 0,01 à 0,5% en poids dudit agent d'ajustement du pH basique.
6. Lingette à essuyer selon l'une quelconque des revendications 1 à 5, dans laquelle le substrat est un non tissé, comprenant de préférence des fibres cellulaires.
7. Lingette à essuyer selon l'une quelconque des revendications 1 à 6, comprenant ladite composition en quantité de 2 à 8 fois le poids sec dudit substrat.
8. Composition en émulsion appropriée pour le nettoyage ou le traitement de la peau d'une personne, la composition étant caractérisée en ce qu'elle comprend:  
 (a) au moins 90% en poids, de préférence 91 à 99% en poids, d'eau;  
 (b) 0,5% à 2,5% en poids d'une huile de silicone;  
 (c) un émulsifiant de type polymère d'acide carboxylique comprenant un polymère réticulé alkyle en C<sub>10</sub>-C<sub>30</sub>-acrylates, en quantité efficace pour émulsionner ladite huile dans ladite eau, de préférence à raison de 0,05 à 1% en poids; et  
 (d) une quantité efficace, de préférence 0,05 à 0,5% en poids, d'un agent antimicrobien comprenant un mélange de 1,3-bis(hydroxyméthyl)-5,5-diméthylhydantoïne et de butylcarbamate de 3-iodo-2-propynyle.
9. Composition selon la revendication 8, comprenant en outre:  
 (e) une quantité efficace, de préférence 0,5 à 3% en poids, d'un polyol soluble dans l'eau choisi dans le groupe constitué par les alkylènepolyols solubles dans l'eau, les esters d'alkylènepolyols solubles dans l'eau, et leurs mélanges;  
 (f) une quantité efficace, de préférence 0,01 à 0,2% en poids, d'un agent chélatant; et  
 (g) une quantité efficace, de préférence 0,01 à 0,5% en poids, d'un agent d'ajustement du pH basique.
10. Procédé pour produire la composition en émulsion selon la revendication 8, dans lequel ladite composition est formée par addition en une étape et mélange de chacun des ingrédients.
11. Procédé selon la revendication 10, dans lequel ladite composition comprend par ailleurs, un agent antimicrobien, un agent chélatant et un agent d'ajustement du pH, dans lequel ledit procédé comprend les étapes consistant à combiner d'abord au moins une partie de l'eau, ledit émulsifiant, ladite huile de silicone, ledit agent antimicrobien et ledit agent chélatant pour former une émulsion, puis à ajouter ledit agent d'ajustement du pH.
12. Procédé selon la revendication 10, dans lequel lesdits ingrédients de ladite composition sont mélangés, la vitesse du moteur étant réglée de manière à entraîner un arbre libre à une vitesse de 1 000 tours/min à 6 000 tours/min pendant 5 à 60 minutes.